SAFETY DATA SHEET

AB03 - NON SIL 200 RELEASE AGENT

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier Product name Non Sil 200 Release Agent Product number AB03 1.2. Relevant identified uses of the substance or mixture and uses advised against Identified uses Cleaning agent. Uses advised against Use only for intended applications. 1.3. Details of the supplier of the safety data sheet Supplier CGP Chemicals Ltd Unit 6 Northside Business Park Hawkins Lane Burton on Trent Staffordshire **DE14 1DB** (01283) 511101 sales@cgpchemicals.co.uk 1.4. Emergency telephone number Emergency telephone (01283) 511101

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture Classification (EC 1272/2008)

Physical hazards Health hazards Aerosol 1 - H222, H229 Skin Irrit. 2 - H315 STOT SE 3 -H336 Aquatic Chronic 2 - H411

Environmental hazards 2.2. Label elements

Hazard pictograms





Danger

Signal word Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with

long lasting effects.

	ADUS – NON SIL ZUU RELEASE AGENT
Precautionary	P102 Keep out of reach of children.
statements	P261 Avoid breathing vapour/ spray.
	P271 Use only outdoors or in a well-ventilated area.
	P280 Wear protective gloves/ protective clothing/ eye
	protection/ face protection.
	P302+P352 IF ON SKIN: Wash with plenty of water.
	P332+P313 If skin irritation occurs: Get medical advice/
	attention.
	P501 Dispose of contents/ container in accordance with
	local regulations.
Contains	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics,
Cumplementer :	<5% n-hexane
Supplementary precautionary	P210 Keep away from heat, hot surfaces, sparks, open
statements	flames and other ignition sources. No smoking.
Statements	P211 Do not spray on an open flame or other ignition
	source.
	P251 Do not pierce or burn, even after use.
	P304+P340 IF INHALED: Remove person to fresh air
	and keep comfortable for breathing.
	P312 Call a POISON CENTRE/doctor if you feel unwell.
	P362+P364 Take off contaminated clothing and wash it before reuse.
	P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
2.3. Other hazards	temperatures exceeding 50 0/122 1.
This product does n	ot contain any substances classified as PBT or vPvB.
SECTION 3: Comp	osition/information on ingredients
OLOTION 3. Compo	
3.2. Mixtures	

Petroleum gases, liquefied			30- < 60%
CAS number: 68476-85-7	EC number: 270-704-2		
Classification			
Flam. Gas 1A - H220			
Press. Gas (Liq.) - H280			
			30- < 60%
Hydrocarbons, C6-C7, n-alkanes, isoalk	anes, cyclics, <5% nhexane		
CAS number: —	EC number: 921-024-6	REACH registration number: 012119475514-35-XXXX	
Classification			
Flam. Liq. 2 - H225			
Skin Irrit. 2 - H315			
STOT SE 3 - H336 Asp. Tox. 1 - H304			
Aquatic Chronic 2 - H411			
n-hexane			<1%
CAS number: 110-54-3	EC number: 203-777-6		

Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361f STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms are severe or persist. Place unconscious person on their side in the recovery position and ensure breathing can take place.
Ingestion	Rinse mouth thoroughly with water. If in doubt, get medical attention promptly. Due to the small packaging, the risk of ingestion is minimal. Do not induce vomiting unless under the direction of medical personnel.
Skin contact	Remove contamination with soap and water or recognised skin cleansing agent.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse with water. Get medical attention if any discomfort continues.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.
4.2. Most important symptoms	and effects, both acute and delayed
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Spray/mists may cause respiratory tract irritation.
Ingestion	Due to the physical nature of this product, it is unlikely that ingestion will occur.
Skin contact	Repeated exposure may cause skin dryness or cracking.
Eye contact	Vapour or spray in the eyes may cause irritation and smarting. Particles in the eyes may cause irritation and smarting.
4.3. Indication of any immediate	e medical attention and special treatment needed
Specific treatments Treatments	at symptomatically.
SECTION 5: Firefighting measu	Ires
5.1. Extinguishing media	

Suitable extinguishing mediaThe product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder
or water fog.Unsuitable extinguishing
mediaDo not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Vapours may form explosive mixtures with air.

Hazardous combustion products	AB03 – NON SIL 200 RELEASE AGENT Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours. Carbon monoxide (CO). Carbon dioxide (CO2).		
5.3. Advice for firefighters			
Protective actions during firefighting	Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control runoff water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.		
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.		
SECTION 6: Accidental releas	e measures		
6.1. Personal precautions, pro	tective equipment and emergency procedures		
Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Evacuate area. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Take precautionary measures against static discharges.		
6.2. Environmental precaution	6.2. Environmental precautions		
Environmental precautions	Avoid discharge into drains or watercourses or onto the ground. Not considered to be a significant hazard due to the small quantities used.		
6.3. Methods and material for	containment and cleaning up		
Methods for cleaning up	Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Under normal conditions of handling and storage, spillages from aerosol containers are unlikely. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Provide adequate ventilation. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.		
6.4. Reference to other section	<u>15</u>		
Reference to other sections	For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.		
SECTION 7: Handling and sto	rage		
7.1. Precautions for safe hand	ling		
Usage precautions	Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. The product is flammable. Avoid exposing aerosol containers to high temperatures or direct sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Do not expose to temperatures exceeding 50°C/122°F. Avoid inhalation of vapours and spray/mists. Avoid contact with eyes.		

Advice on general Good personal hygiene procedures should be implemented. Wash contaminated skin thoroughly after handling. Take off contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product. Wash after use and before eating, smoking and using the toilet.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions	Store away from incompatible materials (see Section 10). Keep away from oxidising materials, heat and flames. Store in a cool and well-ventilated place. Protect from sunlight. Keep containers upright. Protect containers from damage. Do not expose to temperatures exceeding 50°C/122°F. Do not store near heat sources or expose to high temperatures. Store in accordance with national regulations.	
Storage class	Chemical storage. Aerosol containers and lighters	
7.3. Specific end use(s)		
Specific end use(s)	The identified uses for this product are detailed in Section 1.2.	
SECTION 8: Exposure controls/Personal protection		
8.1. Control parameters Occupational exposure limits		

Petroleum gases, liquefied

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³ Short-

term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³ n-hexane

Long-term exposure limit (8-hour TWA): WEL 20 ppm 72 mg/m³ WEL = Workplace Exposure Limit.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

DNEL

Workers - Inhalation; Long term systemic effects: 2035 mg/m³ Workers - Dermal; Long term systemic effects: 773 mg/kg/day General population - Inhalation; Long term systemic effects: 608 mg/m³ General population - Dermal; Long term systemic effects: 699 mg/kg/day General population - Oral; Long term systemic effects: 699 mg/kg/day

8.2. Exposure controls



Appropriate engineering ingredients.	Provide adequate ventilation. Observe any occupational exposure limits for the product or controls
Eye/face protection	Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses. Personal protective equipment for eye and face protection should comply with European Standard EN166.
Hand protection	To protect hands from chemicals, gloves should comply with European Standard EN374. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.
Other skin and body protection	Wear appropriate clothing to prevent repeated or prolonged skin contact.
Hygiene measures	Wash after use and before eating, smoking and using the toilet. Do not eat, drink or smoke when using this product.

Respiratory protection

AB03 – NON SIL 200 RELEASE AGENT

Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with European Standard EN14387. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

SECTION 9: Physical and chemical properties		
9.1. Information on basic phys	sical and chemical properties	
Appearance	Aerosol.	
Colour	Clear.	
Odour	Organic solvents.	
Initial boiling point and range	-402°C (LPG)	
Flash point	-104°C (LPG)	
Upper/lower flammability or explosive limits	1.4 - 10.9%(V)(LPG)	
Auto-ignition temperature	365 °C / 689 °F (LPG)	
9.2. Other information		
SECTION 10: Stability and rea	activity	
10.1. Reactivity		
Reactivity	See the other subsections of this section for further details.	
10.2. Chemical stability		
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.	
<u>10.3. Possibility of hazardous r</u> Possibility of hazardous reactions	reactions The following materials may react strongly with the product: Oxidising agents.	
10.4. Conditions to avoid		
Conditions to avoid	Avoid exposing aerosol containers to high temperatures or direct sunlight. Pressurised container: may burst if heated Avoid heat, flames and other sources of ignition. Avoid the following conditions: Freezing.	
10.5. Incompatible materials		
Materials to avoid	No specific requirements are anticipated under normal conditions of use.	
10.6. Hazardous decomposition products		
Hazardous decomposition Does not decompose when used and stored as recommended. Thermal decomposition or products combustion products may include the following substances: Harmful gases or vapours.		

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation

Gas or vapour may irritate the respiratory system. May cause nausea, headache, dizziness and intoxication. Vapour may irritate respiratory system/lungs.

Ingestion	AB03 – NON SIL 200 RELEASE AGENT Due to the physical nature of this product, it is unlikely that ingestion will occur. Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract. May cause chemical burns in mouth, oesophagus and stomach. May cause discomfort if swallowed. May cause stomach pain or vomiting.
Skin contact	Repeated exposure may cause skin dryness or cracking.
Eye contact	May cause eye irritation. May cause serious eye damage.
Route of exposure	Inhalation Ingestion Skin and/or eye contact
SECTION 12: Ecological infor	mation
<u>12.1. Toxicity</u>	
Toxicity	The product is not believed to present a hazard due to its physical nature.
12.2. Persistence and degrada	ability
Persistence and degradability	Volatile substances are degraded in the atmosphere within a few days. The other substances in the product are expected to be readily biodegradable.
12.3. Bioaccumulative potentia	al
Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water-solubility of this product. Exposure to aquatic environment unlikely.
12.4. Mobility in soil	
Mobility	The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.
12.5. Results of PBT and vPvI	B assessment
Results of PBT and vPvB assessment	This substance is not classified as PBT or vPvB according to current EU criteria.
12.6. Other adverse effects	
Other adverse effects	The product contains volatile organic compounds (VOCs) which have a photochemical ozone creation potential.
SECTION 13: Disposal consid	lerations
13.1. Waste treatment method	<u>ls</u>
General information	The generation of waste should be minimised or avoided wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Dispose of waste product or used containers in accordance with local regulations
Disposal methods	Do not empty into drains. Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Waste class	The waste code classification is to be carried out according to the European Waste Catalogue (EWC).
SECTION 14: Transport inform	nation
<u>14.1. UN number</u> UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (ADN)	1950

14.2. UN proper shipping name		
Proper shipping name (ADR/RID)	AEROSOLS	
Proper shipping name (IMDG) AEROSOLS		
Proper shipping name (ICAO)	AEROSOLS	
Proper shipping name (ADN)	AEROSOLS	
14.3. Transport hazard class(es)ADR/RID class2.1		
ADR/RID classification code	5F	
ADR/RID label	2.1	
IMDG class	2.1	
ICAO class/division	2.1	
ADN class	2.1	

Transport labels



ADR/RID packing group	None
IMDG packing group	None
ICAO packing group	None
ADN packing group	None
14.5. Environmental hazards	

Environmentally hazardous substance/marine pollutant No.

14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and e	nvironmental regulations/legislation specific for the substance or mixture
National regulations	Health and Safety at Work etc. Act 1974 (as amended).
	The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment
	Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].
	EH40/2005 Workplace exposure limits.
	The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18
	December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of
	Chemicals (REACH) (as amended).
	Commission Regulation (EU) No 2015/830 of 28 May 2015.
	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16
	December 2008 on classification, labelling and packaging of substances and mixtures
	(as amended).
	Council Directive of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers (75/324/EEC) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

EU - EINECS/ELINCS None of the ingredients are listed or exempt.

SECTION 16: Other information	n
Abbreviations and acronyms used in the safety data sheet	ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways. RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail. IATA: International Air Transport Association. ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air. IMDG: International Maritime Dangerous Goods. CAS: Chemical Abstracts Service. ATE: Acute Toxicity Estimate. LC ₅₀ : Lethal Concentration to 50 % of a test population. LD ₅₀ : Lethal Dose to 50% of a test population. LD ₅₀ : Lethal Dose to 50% of a test population. PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative.
Classification abbreviations and acronyms	Aerosol = Aerosol
Key literature references and sources for data	Source: European Chemicals Agency, http://echa.europa.eu/
Classification procedures according to Regulation (EC) 1272/2008	Aerosol 1 - H222, H229: : Expert judgement.
Revision date	19/01/2021
Revision	1
SDS number	8201

Hazard statements in full	 H220 Extremely flammable gas. H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H229 Pressurised container: may burst if heated. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H361f Suspected of damaging fertility.
	5

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.